reflex 14 + reflex 25

ADDITIONAL COLOUR AND FINISH CHARGE (see new colour chart)

The additional charges are calculated on the base price of RAL 9010.

C0 Category without any additional charge (RAL 9010)

C1 Category +10%
C2 Category +15%
C3 Category +20%
RAL colours not included in the colour chart +30%

Colours according to samples request feasibility and cost estimate

PLATED finishes NOT available

SUPPORTS

The radiators are supplied with standard supports (code ST) that include wall fixing shelves. On request you can order them with bracket supports permanently welded on the radiators, which must be specified when placing the order and have the following code and cost:

Right side WALL bracket supports
Left side WALL bracket supports
NOT available
CEILING bracket supports
NOT available


LIMITS

WALL bracket supports RF14 (Max. Length 53,8 cm) RF14D NOT available RF25 (Max. Length 56,0 cm) RF25D NOT available CEILING bracket supports RF14 (Max. Length 73,0 cm) (Max. Length 53,8 cm) RF14D RF25 (Max. Length 80,5 cm) RF25D (Max. Length 56,0 cm)

PACKING

The cardboard packing box is included in the price of sale of the products, and for the REFLEX model it contains the complete wall fixing kit and the manual vent valve. The support shelves for the radiators MUST NOT be recessed in the wall but must be installed with expansion screws.

0 34 E H H 5,0 5,0 5,0




CONNECTORS

The standard REFLEX models are always supplied with "0C1" connectors (see below – connectors diagram)
Should different connectors be required, such connectors must be strictly specified in the order.

In the case of "0B2" connectors, the radiator can be equipped with 2 1/8" chrome-plated plugs on the head of the manifolds.


Standard connectors

standard connector always supplied, if not otherwise specified in the order




Custom-made connectors

Connectors available on request WITH additional charge of €




Connectors on request

Connectors available on request WITHOUT any additional charge



Custom-made connectors

Connectors available on request WITH additional charge of €



B2M

Specify "d" and "i"

Watt = Kcal/h \div 0,860 reflex 14 $Kcal/h = Watt \times 0,860$

Price for items with White RAL 9010 finish and standard connectors, VAT and transport costs not included For correction factors different to ΔT 50°C see page 209 To help you properly fill out the code relative to the item requested see code examples on page 5

RF1	4
-----	---

L mirror (cm)	L (cm)	H (cm)	Watts ΔT 50°C Coloured version	Category C0 RAL 9010 (€)	Category C1 (€)	Category C3 (€)	Water Content (I)
14	44,2	180	665				2,484
14	53,8	180	887				3,312
14	63,4	180	1108				4,140
14	44,2	200	731				2,712
14	53,8	200	975				3,616
14	63,4	200	1219				4,520
24	73,0	180	1108				4,140
24	82,6	180	1330				4,968
24	92,2	180	1553				5,796
24	73,0	200	1219				4,520
24	82,6	200	1463				5,424
24	92,2	200	1706				6,328

RF14D

L mirror (cm)	L (cm)	H (cm)	Watts ∆T 50°C Coloured version	Category C0 RAL 9010 (€)	Category C1 (€)	Category C3 (€)	Water Content (I)
14	44,2	180	984				4,968
14	53,8	180	1312				6,624
14	63,4	180	1640				8,280
14	44,2	200	1080				5,424
14	53,8	200	1441				7,232
14	63,4	200	1800				9,040
24	73,0	180	1640				8,280
24	82,6	180	1967				9,936
24	92,2	180	2295				11,592
24	73,0	200	1800				9,040
24	82,6	200	2160				10,848
24	92,2	200	2520				12,656

Watt = Kcal/h \div 0,860 reflex 25 $Kcal/h = Watt \times 0,860$

Price for items with White RAL 9010 finish and standard connectors, VAT and transport costs not included For correction factors different to ΔT 50°C see page 209

To help you properly fill out the code relative to the item requested see code examples on page 5

RF25

L mirror (cm)	L (cm)	H (cm)	Watts ∆T 50°C Coloured version	Category RAL 9010	Category C3 (€)	Water Content (I)
14	42,5	180	731			6,144
14	49,5	180	914			7,680
14	56,5	180	1096			9,216
14	42,5	200	804			6,784
14	49,5	200	1006			8,480
14	56,5	200	1208			10,176
24	67,0	180	1096			9,216
24	74,0	180	1279			10,752
24	81,0	180	1462			12,288
24	67,0	200	1208			10,176
24	74,0	200	1409			11,872
24	81,0	200	1610			13,568

RF25D

Water Content (I)	Category C3 (€)	Category C1 (€)	Category C0 RAL 9010 (€)	Watts ∆T 50°C Coloured version	H (cm)	L (cm)	L mirror (cm)
12,288				1109	180	42,5	14
15,360				1386	180	49,5	14
18,432				1663	180	56,5	14
13,568				1215	200	42,5	14
16,960				1519	200	49,5	14
20,352				1822	200	56,5	14
18,432				1663	180	67,0	24
21,504				1941	180	74,0	24
24,576				2218	180	81,0	24
20,352				1822	200	67,0	24
23,744				2127	200	74,0	24
27,136				2430	200	81,0	24